






Smart Construction Simulation 2024.1.17(Schedule) About the Release Version







NO.	Target Functions	Overview
2	Machine Simulation (Bug Repair)	<ul style="list-style-type: none">• Overview : Fixed a problem that some points were not shared when copying a runway when the number of points increases.• Details : When copying a runway with many points, some points were not shared. This problem has been corrected so that some points are shared correctly even if the number of points is large when copying a runway. <div><div>Before</div></div> <div><div>After</div></div>



NO.	Target Functions	Overview
3	Machine Simulation (Bug Repair)	<ul style="list-style-type: none">• Overview : Fixed a problem that prevented proper runway copying when a cut/fill area is shared.• Details : When copying a runway that shares a cut/fill area, the point and route of the destination runway would be separated. The problem has been corrected so that copying a runway can be performed normally even if the construction area is shared. <div><div><p>Before</p><p>The point and route are separated.</p></div><div><p>After</p><p>No separation of point and route</p></div></div>




NO.	Target Functions	Overview
4	Machine Simulation (Bug Repair)	<ul style="list-style-type: none">• Overview : Fixed a problem in which runway color changes between load-fit points were not reflected after copying a runway• Details : When changing the runway color after copying a runway, the runway color between load fit points was not reflected. <p>The problem has been corrected so that the runway color is reflected correctly.</p> <div><div>Before</div><div>Change of runway color (red → yellow) is not reflected.</div></div> <div><div>After</div><div>Runway color changes are reflected.</div></div>



NO.	Target Functions	Overview																																																																						
5	Machine Simulation (Function Improvement)	<ul style="list-style-type: none">Overview : Improved dump fuel economy calculations and soil volume per overall fuel economy calculationsDetails : The following two changes have been made to the calculation of soil volume (m3/L) in the cost table. <Change 1> When construction equipment is reused, soil volume (m3/L) and fuel consumption (km/L) are calculated for the first run. <Change 2> Fuel consumption (m3/L) = Total soil volume transported on all routes ÷ Total fuel consumed by all construction equipment.																																																																						
		<div><div><div>Change 1</div><table><tr><th colspan="4">走路1</th></tr><tr><th>稼働率</th><th>燃費 (km/L)</th><th>燃料費 (円)</th><th>土量 (m3/L)</th></tr><tr><td>54.69 (%)</td><td>0.9</td><td>14,616</td><td>2.74</td></tr><tr><td>15.21 (%)</td><td></td><td>11,518</td><td></td></tr></table><div>Fuel consumption and soil volume for the first run were being calculated ⇒Corrected to be calculated based on the total of the relevant runway</div></div><div><div>Change 2</div><table><tr><th colspan="7">集計表 詳細</th></tr><tr><th>名称</th><th>平均単価</th><th>数量</th><th>金額 (円)</th><th>費用計</th><th>金額 (円)</th><th>土量 (m3/L)</th></tr><tr><td>Load capacity: 40t</td><td>75,400 円 / 台日</td><td>2 台日</td><td>150,800</td><td>機械費</td><td>361,400</td><td>2.74</td></tr><tr><td>Bucket capacity: 1.9m3 / Vehicle weight: 45t</td><td>40,300 円 / 台日</td><td>2 台日</td><td>80,600</td><td></td><td></td><td></td></tr><tr><td>Vehicle weight: 100t / Blade width: 5265mm</td><td>65,000 円 / 台日</td><td>2 台日</td><td>130,000</td><td></td><td></td><td></td></tr><tr><td>建機オペレーター</td><td>16,000 円 / 人日</td><td>4 人日</td><td>64,000</td><td>人件費</td><td>64,000</td><td></td></tr><tr><td>消費燃料費</td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>合計</td><td></td><td></td><td></td><td></td><td></td><td>0.83</td></tr></table><div>Calculated with fuel consumed by dump trucks ⇒Corrected to calculate by fuel</div></div></div>	走路1				稼働率	燃費 (km/L)	燃料費 (円)	土量 (m3/L)	54.69 (%)	0.9	14,616	2.74	15.21 (%)		11,518		集計表 詳細							名称	平均単価	数量	金額 (円)	費用計	金額 (円)	土量 (m3/L)	Load capacity: 40t	75,400 円 / 台日	2 台日	150,800	機械費	361,400	2.74	Bucket capacity: 1.9m3 / Vehicle weight: 45t	40,300 円 / 台日	2 台日	80,600				Vehicle weight: 100t / Blade width: 5265mm	65,000 円 / 台日	2 台日	130,000				建機オペレーター	16,000 円 / 人日	4 人日	64,000	人件費	64,000		消費燃料費							合計				
走路1																																																																								
稼働率	燃費 (km/L)	燃料費 (円)	土量 (m3/L)																																																																					
54.69 (%)	0.9	14,616	2.74																																																																					
15.21 (%)		11,518																																																																						
集計表 詳細																																																																								
名称	平均単価	数量	金額 (円)	費用計	金額 (円)	土量 (m3/L)																																																																		
Load capacity: 40t	75,400 円 / 台日	2 台日	150,800	機械費	361,400	2.74																																																																		
Bucket capacity: 1.9m3 / Vehicle weight: 45t	40,300 円 / 台日	2 台日	80,600																																																																					
Vehicle weight: 100t / Blade width: 5265mm	65,000 円 / 台日	2 台日	130,000																																																																					
建機オペレーター	16,000 円 / 人日	4 人日	64,000	人件費	64,000																																																																			
消費燃料費																																																																								
合計						0.83																																																																		



NO.	Target Functions	Overview
6	Machine Simulation (Function Improvement)	<ul style="list-style-type: none">• Overview : Changed dumping capacity formula on work capacity screen of selected machines• Details : Added “÷ Soil Conversion Rate (L)” to the formula for loading capacity (m3) so that the work capacity of dump trucks is calculated by the amount of soil to be loosened. The following displays on the work capacity screen of selected machines have been changed. <div data-bbox="571 678 2184 1324"><p>Added "÷ Soil Conversion Rate (L)" to the calculation formula for loading capacity (m3)</p></div>




NO.	Target Functions	Overview
7	Machine Simulation (Function Improvement)	<ul style="list-style-type: none">• Overview : UI/UX improvement of construction equipment Simulation• Details : The following three changes have been made to improve the UI/UX of Construction Equipment Simulation. <p><Changes></p> <ol style="list-style-type: none">① A dialog box for adding a runway has been added. A screen for adding a new runway based on the information entered after setting the site information, construction equipment settings, and cut and fill areas has been added.② Added a screen for editing foundation data when performing calculations. Added Edit screen for foundation data as a screen for changing foundation information prior to calculation execution③ Changed icon placement Icons are rearranged in consideration of the order/frequency of use, etc. <p>※For details of the above, please refer to the next page and thereafter.</p>




NO.	Target Functions	Overview
7	Machine Simulation (Function Improvement)	<p>① A dialog box for adding a runway has been added. A screen for adding a new runway based on the information entered after setting the site information, construction equipment settings, and cut and fill areas has been added.</p> <p>Addition of a regular runway</p> <p>Additions except for normal runway</p> <p>Set runway information</p> <p>Set construction equipment</p> <p>Set the location of Cut/Fill area</p>



NO.	Target Functions	Overview																										
7	Machine Simulation (Function Improvement)	<p>② Added a screen for editing foundation data when performing calculations. Added Edit screen for foundation data as a screen for changing foundation information prior to calculation execution</p> <div><p>Foundation data can be changed before calculation is performed *Calculated plans cannot be edited (shown on the right)</p><p>After editing basic data Calculations can be performed after editing basic data.</p><table><tr><th colspan="2">基礎データの編集</th></tr><tr><td>対象土密度(t/m3)</td><td>1.8</td></tr><tr><td>バケット係数</td><td>0.85</td></tr><tr><td>掘削難易度係数</td><td>1</td></tr><tr><td>土量換算率L</td><td>1.15</td></tr><tr><td>土量換算率C</td><td>0.9</td></tr></table><table><tr><th colspan="2">基礎データの編集</th></tr><tr><td>工区作業効率</td><td>1.00</td></tr><tr><td>対象土密度(t/m3)</td><td>1.80</td></tr><tr><td>バケット係数</td><td>0.85</td></tr><tr><td>掘削難易度係数</td><td>1.00</td></tr><tr><td>土量換算率L</td><td>1.15</td></tr><tr><td>土量換算率C</td><td>0.90</td></tr></table></div>	基礎データの編集		対象土密度(t/m3)	1.8	バケット係数	0.85	掘削難易度係数	1	土量換算率L	1.15	土量換算率C	0.9	基礎データの編集		工区作業効率	1.00	対象土密度(t/m3)	1.80	バケット係数	0.85	掘削難易度係数	1.00	土量換算率L	1.15	土量換算率C	0.90
基礎データの編集																												
対象土密度(t/m3)	1.8																											
バケット係数	0.85																											
掘削難易度係数	1																											
土量換算率L	1.15																											
土量換算率C	0.9																											
基礎データの編集																												
工区作業効率	1.00																											
対象土密度(t/m3)	1.80																											
バケット係数	0.85																											
掘削難易度係数	1.00																											
土量換算率L	1.15																											
土量換算率C	0.90																											



NO.	Target Functions	Overview
7	Machine Simulation (Function Improvement)	<p>③ Changed icon placement Icons are rearranged in consideration of the order/frequency of use, etc.</p>  <p>Global navigation placement changes</p> <p>Header menu placement change</p>

